

POLYURETHANE IN INTIMATE CONTACT WITH FIBROUS MATERIAL

5

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The invention relates in general to a polymeric compositions containing reinforcement fibers, and a process for the preparation thereof, which products are useful for the formulation of reinforced structures, coatings, liners, and the like. The invention is also directed to an apparatus for and a method of spraying this polymeric compositions, both in the form of a film and a foam.

DESCRIPTION OF RELATED ART

A strong, durable, high build rate coating with no volatile organic compound (VOC) emissions has been desired as a protective coating for many years. Attempts at producing a coating having those characteristics has resulted in compromising one or several of desired properties. Polyurethane polymers, and coatings made from them, result from the reaction of an isocyanate having an isocyanate terminated compound and a polyol having an hydroxyl terminated compound. Polyurethane foams are typically produced by reaction of the polyisocyanate with the polyol in the presence of a blowing agent. Historically, chlorofluorocarbons such as CFC-11 have been the blowing agents of choice. These agents have been thought to negatively affect the environment and are being phased out of the polyurethane foam manufacture.

Low density coatings, when fabricated, tend to have low toughness or abrasion resistance. Furthermore, most coatings require a significant amount of organic solvent to carry the coating during spraying applications, which contributes significantly to the problem of volatile organic compounds (VOC) emissions. Coating compositions must meet with Occupational Safety and Health Administration and the Environment Protection Agency requirements. Since VOCs are typically toxic, smog-producing and noxious, their continued release can cause a detrimental impact on worker safety and on the environment. Governmental regulations restrict the amounts and types of VOCs which are permitted to escape into the atmosphere from coating compositions, therefore, there should preferably be no amount of organic solvents present in coating compositions.

Thick coatings tend to be spongy or brittle and applying that type of coating to a vertical surface is a slow and tedious process due to slumping problems or curing/out gassing times required. The majority of low VOC coatings available at the present time are only acceptable for thin coating applications (less than 20 mils dry film thickness), or have an exceedingly long dry time between applications which prohibits the successful fabrication of high build rate and/or thick coatings. Another disadvantage associated with many of the products prepared in the prior art having high viscosities is that application by spraying is often precluded.

Polymeric resins containing fillers are known, and are described in U. S. Patent No. 5,604,266 to Mushovic. Mushovic discloses a polyester-polyurethane resin material mixed with at least a KEVLAR® filler (manufactured by DuPont). The KEVLAR pulp filler is added to the polyol reactant of the polyurethane. The polyurethane mixture of Mushovic was then poured into a mold. Mushovic does not disclose or suggest a sprayable polymeric

composition containing reinforcing fibers. In the present invention, polymer compositions containing KEVLAR or other reinforcing fibers can be sprayed, while maintaining homogeneity of the composition, necessary for the spray application. Polymer compositions that can be sprayed are more flexible in the field, they can conform to complex shapes and surface details. In order to spray a polymeric composition comprising a reinforcing fiber, such as KEVLAR, SPECTRA® (owned and manufactured by Allied-Signal, Inc., Delaware, U.S.A.), carbon fullerenes and nanotubes, not only must the composition be mixed properly but also requires a modification be made to the dispensing apparatus, i.e. the spray gun. U.S. Patent No. 4,857,569 to Cotts et al., discloses a polymer alloy composition prepared by intimately mixing one or more polyurethane components with selected reinforcing amounts of rod-like aromatic polyamide components (e. g. KEVLAR). However, the compositions of Cotts must be formed either by blending two individual solutions of the polyurethane and rod-like polyamide components in a common or mutually compatible solvent, or by polymerizing the polyurethane components in a solvent, which is itself a solution of the rod-like polyamide component in a suitable solvent. Thus, the KEVLAR reinforcing fiber must be dissolved in a solvent, e.g., a solution of polyparaphenyleneterephthalamide. U. S. Patent Nos. 4,599,401; 4,629,779; 4,707,535; and 4,725,653 to Koleske; U.S. Patent No. 4,857,579 to Domeier and U.S. Patent No. 4,233,205 to O'Connor disclose polyurethane elastomers or other polyurethane products containing KEVLAR fibers. U. S. Patent No. 5,610,224 to DePue et al., discloses an elastic and high strength material formed from polyurethane and aromatic polyamide. Japanese Patent 53-34884 to Masanobu et al., discloses a composite material prepared by curing and bonding an aromatic polyamide fiber and a thermosetting resin with a specific lactam compound and an isocyanate compound.

A hybrid liner is described in U. S. Patent No. 4,956,397 to Rogowski et al., which describes an insulating solid rocket liner made from polyurethane rubber and KEVLAR pulp or fibers, specifically fibrillated fibers. U. S. Patent Nos. 4,034,138 and 4,095,404 to Babayan and U. S. Patent No. 5,120,905 to Cousin et al., all disclose polyurethane material
5 impregnated or coated with aromatic polyamide fibers. U. S. Patent No. 5,167,352 to Robbins and U. S. Patent No. 5,419,139 to Blum et al., both disclose a double wall tank system or a composite cryogenic tank coated or lined with polyurethane and KEVLAR. Blum specifically discloses a tank lined with a laminate of film layers, each having a vacuum deposited metalized coating.

A problem associated with adding a reinforcing fiber, such as KEVLAR, to a polyurethane resin solution has been that the fibers separate out from the polyurethane reaction components, or deteriorate because of the solvents or catalysts in the reaction components, making it impossible to exhibit the intended properties and strength and stability of the added reinforcing fibers. Accordingly, it has conventionally been necessary to agitate
10 the reaction components so as to be uniformly mixed and dispersed, before its use, i.e., before the polyisocyanate and polyol components are mixed together to cause the reaction. Thus, polyurethane resin formed from conventional polyurethane reaction components containing reinforcing fibers cannot be sprayed.

Conventional spray gun assemblies have spring loaded check valves for restricting the
20 flow of two-part reactive polymers. See Figures 1 and 2. U.S. Patent No. 5,810,254 to Kropfield, which describes two premixing chambers, that receive the polymer reaction components, each chamber having an actuating valve for controlling the flow of the components through the premixing chambers. Since two part polyurethanes require a very

specific percentage ratio of the two material components, any significant variation will not produce a polyurethane with the desired cure effectively or quickly, and may not have the desired durability.

5 The ideal polymer for use as a coating or liner would contain reinforcing fibers and other fillers that could be sprayed, would be easy to use, quick to activate, and have a long service life. Polymers that do not have any volatile organic content and do not leak hazardous materials, having zero toxicity, are also necessary for use in coatings and liners. New methods for greatly reducing or eliminating VOCs during the application of such coatings are urgently needed to prevent worker injury and comply with current and pending environmental regulations. Also of great importance is the cost, performance and durability of such polymer formulations. Currently, there does not exist a method of making a polymer composition that satisfies all these criteria.

BRIEF SUMMARY OF THE INVENTION

5 The present invention provides a solvent-free, sprayable polymeric material and a process for preparing a polymer with a fibrous material by providing a predetermined amount of fibrous material, providing reaction components comprising a polyol and an isocyanate, or a combination of a polyurethane with a polyurea, polyester, or epoxy, heating the reaction components, adding the fibrous material to the polyol component, the isocyanate component, or both, and then reacting the reaction components. Another embodiment of the present invention provides a restriction free spray nozzle for mixing and spraying a first reactive polymeric material with a second reactive polymeric material, at least one of the reactive polymeric materials containing a fibrous material, so as to form a two part polymer, the nozzle

20

comprising: a restriction free check valve without springs, a hose for conveying first and second polymeric materials to a ball valve, the nozzle spraying a mixture of the first and second materials from the check valve onto a surface. The nozzle has a large diameter tip of about 0.21 - 0.45 Thousands (thousands of an inch). A mixture of the first and second materials goes through a mixing block and through a static mixer through the nozzle and onto a surface. Another embodiment of the present invention provides a reinforced structure and a method of making the structure. The structure comprises a first and second layer of polyurethane resin containing from about 0.5 to 30% by weight of a fibrous material sandwiching a layer of polyurethane foam containing from about 0.5 to 30% by weight of a fibrous material. A further embodiment of the present invention provides a flexible liner which comprises a porous geotextile fabric, a polyurethane composition comprising a fibrous material sprayed over the geotextile fabric, forming a monolithic membrane with the geotextile fabric.

The products of the present invention are applicable to building elements and articles of manufacture, in particular composite building materials, e.g., coated panel boards, which are lightweight, or as geotextile liners used to line land fills, or for lining/relining pipes. Liners of the present invention have a substantially fluid-tight or leak proof construction, which gives them various useful applications such as improved enclosures for fluid-confining means. Thus, the reinforced fiber polyurethane of the present invention would also have application in the wastewater industry, where polyurethanes have been used extensively since the 1970's. The properties of polyurethanes that are amenable to use in the potable water, hazardous waste, chemical and wastewater industries are their impermeability, resistance to microbial attack, excellent adhesion and abrasion resistance, flexibility, and unlimited film

build. Objects made of steel, iron, plastics and concrete, or objects previously lined with other coatings, may be lined while maintaining the advantageous properties of the polymer, e.g., polyurethanes.

5 The composition of the present invention can be sprayed onto a variety of surfaces to provide abrasion and corrosion resistance, the seamless coating being resistant to many corrosion causing chemicals. Since there is no solvent to evaporate, several cost and time saving advantages accrue. Sandblasting surface preparation of the surface to be coated is avoided, thus, requiring less work, expense and time before application and eliminating waste disposal of the surface preparation materials and any prior coating that was removed. The compositions allow greater thickness per pass, typically 30-40 mils, (solvent systems typically achieve about 4 up to 20 mils), no time lag between coats (solvent systems tend to run); much shorter tack-free times; no inflammable or toxic solvent hazards; no solvent attack on sensitive surfaces; and good adhesion to various substrates. The composition is sprayable at temperatures of about 240°F and above, preferably 140°F and is easily mixed. Moreover, it was unexpectantly found that the coating comprising KEVLAR reinforced fibers was sand-able and, thus, easily repairable.

10
15
20 Foam having reinforced fiber can be used to seal cracks. If the crack already has water in it, the reinforced resin (without adding water) can be sprayed into the crack, react with the water in the crack, creating a foam. Thus, the composition can be applied in concrete reservoirs and parking lots to fill cracks.

It was discovered that polymeric compositions and products coated with the composition did not have the problems associated with conventionally coated products, such as blistering and leaching of volatile organic compounds. Blisters appear in conventional

polymer coatings as raised, localized swellings of the coating, often occur after immersion in liquids, and a viscous acidic liquid is expelled when ruptured. The coating of the present invention solves this problem because it lacks VOCs.

5 The composition of the present invention can also be used to manufacture pipes. Water flowing inside pipes made with the composition of the present invention, comprising KEVLAR, do not have their water flow drag/friction affected by the KEVLAR fibers contained in the composition. Reinforced polyurethane pipes have greater strength and are able to withstand increased, otherwise bursting, pressure. The lower friction inside the pipes decreases costs to supply water to homes.

10 Compositions containing specific reinforcing fibers may be used in applications requiring the properties provided by those fibers and the polymeric composition. For example, ceramic and carbon fibers combined with polyurethane compositions can be used in applications requiring control of thermal expansion.

15 Theses and other features, aspects, and advantages of the present invention will become better understood with regard to the following detailed description, appended claims, and accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a perspective view of a mixing block of the prior art;

20 Figure 2 is an exploded perspective view of the mixing block of Figure 1, showing the elements thereof in greater detail ; and

Figure 3 is an elevational view of the restriction free spray nozzle of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Any of the polyols used in the art to prepare polyurethanes and polyurea-containing polyurethanes or mixtures thereof can be used, for example: a polyol chosen from a variety of -OH terminated polyethers such as the polyoxyalkylene polyols having 2-4 hydroxyl groups and where the alkylene group has 2-6 carbon atoms, obtained by polymerization of an alkylene oxide, such as ethylene oxide, propylene oxide, or butylene oxide, with a glycol; polyethers having higher functionality obtained by reaction with a triol or higher polyol, such as glycerine, trimethylolpropane, and pentaerythritol; and polypropylene-oxide triol, having a preferable molecular weight range of about 300 to 20,000, most preferably 500 to 5000; and aromatic or aliphatic amine-based polyols, and sorbitol based polyether polyols.

The isocyanate component of the polymeric composition may be a diisocyanate or a polyisocyanate. While any suitable polyisocyanate can be used in the foam-making process, readily available industrial polyisocyanates are particularly preferred. Various elastomeric polyurethanes are available from Prime Coatings Incorporated, located in Huntington Beach, U.S.A., under the trademark Utilithane-1600. Other examples of suitable diisocyanates and polyisocyanates useful for making polyurethane foams comprise aromatic, aliphatic and cycloaliphatic polyisocyanates, among others. Representative members of these compounds comprise diisocyanates such as 4,4'-Diphenylmethane-diisocyanate, hexamethylene diisocyanate; m-xylylene diisocyanate; toluene diisocyanate and/or any of its isomers such as 2,4-toluene diisocyanate or commercially available blends of the 2,4- and 2,6-isomers such as the 80:20 and 65:35 blends; polymethylene polyphenylisocyanate; m-phenylene diisocyanate; p-phenylene diisocyanate; 3,3'-dimethyl-4,4'-diphenyl diisocyanate; methylenebis (2-methyl-p-phenylene) diisocyanate; 3,3'-dimethoxy-4,4'-biphenylene diisocyanate; 2,2',4,4'-

tetramethyl-4,4'-biphenylene diisocyanate; 3,3'-dimethyl-4,4'-diphenylmethane diisocyanate; 4,4'-diphenylisopropylidene diisocyanate; 1,5'-naphthylene diisocyanate; and polymethylene polyphenylisocyanate. The ratio of equivalents of isocyanates, side A components, to polyols, side B components is from about 10 to 1 by volume, preferably from about 3 to 1, most preferably from about 1 to 1.

The structure of KEVLAR is unique in that it is an organic fiber that is crystalline with a high degree of orientation. KEVLAR pulp is produced by fracturing this crystalline structure. Pulp products are very short, highly fibrillated fibers. The amount of KEVLAR used is based on its total weight percent of the polymeric composition (the mixture of component/side A and component/side B reagents), and is preferably added in the amount of about 0.50 weight % to 30 weight % of the total weight percent of the polymeric composition, preferably about 0.50 weight % to 1.00 weight %, most preferably about 0.50 weight % to 0.75 weight %, for applications using a spray gun. The amount of added reinforcing fiber, e.g., KEVLAR, may be easily increased for hand applications and the higher end of the previously disclosed range may be used, e.g., about 30 weight %. If the KEVLAR is separately added to component A and component B, the KEVLAR added to component A plus the KEVLAR added to component B is about 0.50 weight % to 30 weight % of the total weight percent of the polymeric composition, preferably about 0.50 weight % to 0.75 weight %. When the KEVLAR is added to both components A and B, it is preferably added to component A in an equal weight percent amounts to that added to component B. However any amount may be added to the components individually as long as the total amount of KEVLAR added is about 0.50 weight % to 30 weight % of the total weight percent of the polymeric composition. Other fibers could be used to substitute for the KEVLAR, such as

SPECTRA, glass and ceramic fibers, carbon fullerenes, and carbon nanotubes and can be added in the same amounts.

Catalysts can be added which promote the formation of polyurethane by reaction of the isocyanate groups and hydroxy groups. For example, amine compounds, such as triethanolamine, triethylenediamine, N-methylmorpholine, tetramethyl-1,4-butanediamine, N-methylpiperazine, dimethylethanolamine, and diethylethanolamine, triethylamine; and organometallic compounds, such as stannous octanoate, dibutyltin dilaurate, and dibutyltin di-2-ethylhexanoate. These catalysts may be used alone or in combination with one another. Amounts used are 1:1-10:1 by weight ratio of the catalyst: polymeric composition inclusive of the reinforcing fibers.

It is often desirable to employ minor amounts of certain other compounds in preparing the polymer composition, such as: one or more catalysts, surfactants, fire retardants, preservatives, pigments (including titanium or aluminum dioxide, and high UV absorbing ultra-fine titanium dioxide), antioxidants, anti-microbial agents, filler, and anti-static agents, powdered tungstun. Amounts used can be up to 25% by volume of the total weight of the polymer composition.

Spraying the polymeric film/foam compositions of the present invention begins when the fibrous material is pre-weighed to the total weight of polymeric composition (e.g., the polyurethane) desired, as discussed above. It is preferable to use fibrous material that is dry, such as by heating it to a temperature of from about 140° to 160°F, prior to adding the fibrous material to the reaction components A and/or B. Component A and B are heated to a temperature of about 160°F to 250°F. About 10 Volume % of Component A is added with the pre-weighed fibrous material, or 10 Volume % of Component B is added to the pre-

weighed fibrous material, or both components are added/blended with the predetermined total weight % of the fibrous material for about fifteen minutes under anhydrous conditions, preferably under an inert atmosphere such as a nitrogen blanket. The adding of the fibrous material to the polyol, the isocyanate, or both, is such that the fibrous material is mixed randomly within the polyol, the isocyanate, or both. The separate components, one or both of which contain the fibrous material are packaged under anhydrous conditions, preferably under an inert atmosphere such as a nitrogen blanket, until ready for use/application. If the composition of the present invention is sprayed in multiple applications, it is preferable to follow the first application while it is still in a soft liquid phase, whereby to allow the polymer to cross-link, enabling the fibrous material to embed in both the layer of the first application and any following applications.

Application of the polymeric composition begins when component A reagent is supplied by pump to a metering unit, or a metering pump. Component B containing polyol, catalysts, or surfactants is then prepared according to a defined formulation in a mix tank. Either or both component A or B contains the fibrous material. Any additional blowing agents, e.g. water or an alcohol/water mixture may be either added to component B, prior to its reaction with component A, or may be added to the mixture of component A and component B. Component B is also supplied by pump to a metering unit, or a metering pump. The metering pumps boost the pressure generally to 2000 to 2500 psi and control the flow of components A and B to a precise ratio as determined by the desired chemistry. The ratio of isocyanates, side A components, to polyols, side B components is from about 10 to 1 by volume, preferably from about 3 to 1, most preferably from about 1 to 1. The pumps deliver components A and B to at least one mixing block. Inside the mixing block, components A

and B are statically mixed at high pressure, which results in intimate mixing of the components. The mixed components travel through an input hose (12) to the ball valve (10) through the restriction free check valve (20), a check valve without the spring (22) of the prior art check valve, through the spray tip (30), seen in Figure 3. The pot life or working time of the mixed polymeric composition is variable, but is typically short. The mixed chemicals begin to react in about 3 seconds following mixing and completing reaction in about 3-30 minutes.

The polymeric composition of the present invention may be sprayed in any thickness, typically of about 2000 mils to 10 mils in one application, depending on the project needs. The polymeric foam of the present invention can be sprayed into a mold, either in normal atmospheric conditions or under 2-3 atm of pressure.

The geotextile fabric is porous such that the polyurethane can fill in the pores and it becomes one-layer.

Surface preparation

Conventional coating processes require expensive and labor intensive surface preparation. For example, steel surfaces typically require abrasive sand blast cleaning to near white, which necessitates expensive removal of oftentimes hazardous materials. However, the present invention requires little or no surface preparation. Deteriorated concrete surfaces should be prepared by high-pressure water blasting to a sound concrete surface that is free of oil, grease, or existing coatings.

The following examples are given to illustrate the invention.

Example 1

KEVLAR was pre-weighed to the 0.75 weight percent of the total weight desired of the final polyurethane material. The side A reaction component, a diisocyanate (4,4'-Diphenylmethane-diisocyanate) and the side B reaction component, a blend of hydroxy-terminated polyols found in Utilithane 1600 manufactured by Prime Coatings, Inc.,
5 Huntington Beach, U.S.A., were heated to a temperature of about 160°F. Under an inert atmosphere of nitrogen, ten percent by volume of the diisocyanate was added to and mixed for about fifteen (15) minutes with the pre-weighed KEVLAR pulp, in order to wet the KEVLAR fibers. The remaining amount of the diisocyanate was added to the diisocyanate containing
10 the pre-wetted KEVLAR fibers, and was mixed for about thirty (30) minutes under an inert atmosphere of nitrogen. The remaining amount of polyol was added to the polyol containing the pre-wetted KEVLAR fibers, and was also mixed for about thirty (30) minutes under an inert atmosphere of nitrogen. The diisocyanate and polyol containing KEVLAR were packaged separately under an inert atmosphere of nitrogen until needed for application. The
15 diisocyanate and the polyol were in an about 1:1 ratio by volume.

Example 2

The procedures of Example 1 were followed substituting 1.0 weight % KEVLAR pulp for the 0.75 weight %.

Example 3

The procedures of Example 1 were followed substituting bringing the temperatures of the diisocyanate and polyol reagents to about 250°F, prior to adding the pre-weighed KEVLAR pulp.

5

Example 4

The procedures of Example 1 were followed adding the step of dry-heating the pre-weighed KEVLAR pump to a temperature of about 160°F, prior to adding to the 10% diisocyanate and polyol reagents.

Example 5-8

The procedures of Example 1 can be followed by substituting, respectively, about 0.5 to 0.75 weight % of the following: high molecular weight polyethylene fibers, such as SPECTRA fibers; fullerenes; nanotubes; ceramic fiber, for the KEVLAR pulp fibers.

Example 9

The procedures of Example 1 were followed substituting 30 weight % KEVLAR for the 0.75 weight % KEVLAR.

Example 10

The procedures of Example 1 were followed by substituting the step of adding the pre-weighed KEVLAR pulp to 100% of the diisocyanate and polyol reagents and blending for

20

about thirty (30) minutes, for the steps of adding the KEVLAR to ten (10)% of the diisocyanate and polyol reagents.

Example 11

5 The procedures of Example 1 were followed by substituting the step of adding the pre-weighed KEVLAR pulp to ten % of the diisocyanate reagent only, for the step of adding the pre-weighed KEVLAR pulp to ten % of the diisocyanate and ten % of the polyol reagents.

Example 12

10 The procedures of Example 1 were followed by substituting the step of adding the pre-weighed KEVLAR pulp to ten % of the polyol reagent only, for the step of adding the pre-weighed KEVLAR pulp to ten % of the diisocyanate and ten % of the polyol reagents.

Example 13

15 The diisocyanate and polyol reagents containing KEVLAR made from the procedures of Example 1 were followed to create the polyurethane foam containing KEVLAR of the present invention. A predetermined amount of water (e.g., 0.5% by volume) was added to the polyol reaction component, creating a foam. The predetermined amount depends on the needed density of the resulting foam.

Example 14

The procedures of Example 13 can be followed substituting the step of adding water to the polyol reaction component for the step of injecting water as a third component, before the mixer, at an equal pressure to the two other reagents (the polyol and the isocyanate).

5

Example 15

A porous geotextile sheet of about 1/8" to 3/16" manufactured by Geotextile was used to line a concrete surface. The concrete surface was prepared by pressure wash. The KEVLAR containing polyurethane film of the present invention was sprayed onto the porous geotextile mat which formed a monolithic membrane with the geotextile mat. The perimeter edges of the sheet were sprayed with the polyurethane to attach the sheet to the surface.

Example 16

A method of applying the composition of the present invention to line an old tank concrete was carried out. The surface of the tank was prepared by pressure washing (<1000 psi) with water to clean the surface. A thin layer of about 20 mils of polyurethane without the reinforcing fiber was sprayed onto the tank surface, which served to seal in volatile organic compounds leaking from the previous liner. The diisocyanate composition containing 1.00 weight % KEVLAR was supplied by pump to a metering pump. The polyol composition containing 1.00 weight % KEVLAR was also supplied by pump to a metering pump. The metering pumps boosted the pressure to about 2000 to 2500 psi and controlled the flow of the diisocyanate and polyol to a ratio of about 1:1. The pumps delivered the diisocyanate and polyol containing KEVLAR to at least one foam/film mixhead. Inside the mixhead, the

Components A(diisocyanate) and B(polyol) were impinged against each other at high pressure, which resulted in intimate mixing of the components, forming a sprayable polyurethane containing KEVLAR. The polyurethane containing KEVLAR was then sprayed in a single application over the tacky underlying layer of about 20 mils, thereby fusing with the underlying layer. The polyurethane layer containing the KEVLAR was applied in a coating of about 100 mils.

Example 17

A reinforced polymeric panel was manufactured. A sheet of polyethylene was laid down in a container. 20 mils of the composition made in Example 1 was sprayed on top of the polyethylene sheet, while still tacky (about 1 minute), a polyurethane foam of Example 13 was sprayed at about 20 to 100 mils. The foam was sprayed while the resin layer was still tacky so that the polyurethane layers cross-linked and the KEVLAR fibers contained in both the resin and foam, embedded within both layers. The polyethylene sheet was removed (peeled off) and the panel was planed.

Example 18

A reinforced construction panel was made by spraying a layer of polyurethane (as described in Example 1) in a mold 20-2000 mils thick, while it was still tacky (about 3 minutes) the polyurethane foam of Example 13 was sprayed at a predetermined thickness. Thickness is dependent on the application of the panel are there are no limits to how thick to spray the foam. The polyurethane resin material contained KEVLAR, and was sprayed on both the top and bottom sides of the panel.

Example 19

The panels of Example 17 and 18 can be pre-threaded for future use in attaching the panels to other objects. A fastener is attached to the polyurethane layer prior to spraying the polyurethane foam. Spraying the polyurethane foam. After the foam is set, the fastener is removed, leaving a hole of a predetermined diameter, for use subsequent attachment of the panel.

Example 20

Pipes can be made of the polymeric resin of Example 1. A mold of predetermined length and diameter is placed on a lathe. A hose can be suspended above the lathe and mold and to run parallel to the length of the mold. The hose either can have predetermined spaced spray tips for allowing the polymeric material to be sprayed or can have at least one spray tip which is moved above and along the length of the mold. The polymeric material of Example 1 can be sprayed through the spray tips, for a predetermined amount of time while the mold is spun on the lathe to form a pipe of predetermined thickness.

The following references are incorporated herein by reference: U.S. Patent No. 5,604,266 to Mushovic; U.S. Patent to Cotts et al., 4,857,569; U.S. Patent Nos. 4,599,401; 4,629,779; 4,707,535; and 4,725,653 to Koleske; U.S. Patent No. 4,857,579 to Domeier; U.S. Patent No. 4,233,205 to O'Connor; U.S. Patent No. 5,610,224 to DePue et al.; Japanese Patent 53-34884 to Masanobu et al.; U.S. Patent No. 4,956,397 to Rogowski et al.; U.S. Patent Nos. 4,034,138 and 4,095,404 to Babayan; U.S. Patent No. 5,120,905 to Cousin et al.; U.S. Patent No. 5,167,352 to Robbins; U.S. Patent No. 5,419,139 to Blum et al.; and U.S. Patent No. 5,810,254 to Kropfield.

Although the foregoing invention has been described in some detail by way of illustration and example for purposes of clarity and understanding, it will be obvious that various modifications and changes which are within the knowledge of those skilled in the art are considered to fall within the scope of the appended claims.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230